

CS W186 - Spring 2020

Guerrilla Section 3

Joins and Query Optimization

Sunday, March 15, 2020

Joins

We will be joining two tables: a table of students, and a table of assignment submissions; and we will be joining by the student ID:

```
CREATE TABLE Students (  
    student_id INTEGER PRIMARY KEY,  
    ...  
);  
  
CREATE TABLE AssignmentSubmissions(  
    assignment_number INTEGER,  
    student_id INTEGER REFERENCES Students(student_id),  
    ...  
);  
  
SELECT *  
FROM Students, AssignmentSubmissions  
WHERE Students.student_id = AssignmentSubmissions.student_id;
```

We also have:

- `Students` has $[S] = 20$ pages, with $p_S = 200$ records per page
- `AssignmentSubmissions` has $[A] = 40$ pages, with $p_A = 250$ records per page

Questions:

1. What is the I/O cost of a simple nested loop join for `Students` \bowtie `AssignmentSubmissions`?

2. What is the I/O cost of a simple nested loop join for `AssignmentSubmissions` \bowtie `Students`?

3. What is the I/O cost of a block nested loop join for `Students` \bowtie `AssignmentSubmissions`?
Assume our buffer size is $B = 12$ pages.

4. What about block nested loop join for `AssignmentSubmissions` \bowtie `Students`?
Assume our buffer size is $B = 12$ pages.

5. What is the I/O cost of an Index-Nested Loop Join for `Students` \bowtie `AssignmentSubmissions`?
Assume we have a **clustered** alternative 2 index on `AssignmentSubmissions.student_id`, in the form of a height 2 B+ tree. Assume that index node and leaf pages are not cached; all hits are on the same leaf page; and all hits are also on the same data page.

6. Now assume we have a **unclustered** alternative 2 index on `AssignmentSubmissions.student_id`, in the form of a height 2 B+ tree. Assume that index node pages and leaf pages are never cached, and we only need to read the relevant leaf page once for each record of `Students`, and all hits are on the same leaf page.

What is the I/O cost of an Index-Nested Loop Join for `Students` \bowtie `AssignmentSubmissions`?

HINT: The foreign key in `AssignmentSubmissions` may play a role in how many accesses we do per record.

7. What is the cost of an unoptimized sort-merge join for `Students` \bowtie `AssignmentSubmissions`?
Assume we have $B = 12$ buffer pages.

8. What is the cost of an **optimized** sort-merge join for `Students` \bowtie `AssignmentSubmissions`?
Assume we have $B = 12$ buffer pages.

9. In the previous question, we had a buffer of $B = 12$ pages. If we shrank B enough, the answer we got might change.

How small can the buffer B be without changing the I/O cost answer we got?

10. What is the I/O cost of Grace Hash Join on these tables?

Assume we have a buffer of $B = 6$ pages.

Query Optimization 1

(Modified from Fall 2017)

For the following question, assume the following:

- Column values are uniformly distributed and independent from one another

- Use System R defaults (1/10) when selectivity estimation is not possible
- Primary key IDs are sequential, starting from 1
- Our optimizer does not consider interesting orders

We have the following schema:

Table Schema	Records	Pages	Indices
CREATE TABLE Student (sid INTEGER PRIMARY KEY, name VARCHAR(32), major VARCHAR(64), semesters_completed INTEGER)	25,000	500	<ul style="list-style-type: none"> • Index 1: Clustered(major). There are 130 unique majors • Index 2: Unclustered(semesters completed). There are 11 unique values in the range [0, 10]
CREATE TABLE Application (sid INTEGER REFERENCES Student, cid INTEGER REFERENCES Company, status TEXT, (sid, cid) PRIMARY KEY)	100,000	10,000	<ul style="list-style-type: none"> • Index 3: Clustered(cid, sid). • Given: status has 10 unique values
CREATE TABLE Company (cid INTEGER PRIMARY KEY, open_roles INTEGER)	500	100	<ul style="list-style-type: none"> • Index 4: Unclustered(cid) • Index 5: Clustered(open roles). There are 500 unique values in the range [1, 500]

Consider the following query:

```

SELECT Student.name, Company.open_roles, Application.referral
FROM Student, Application, Company
WHERE Student.sid = Application.sid           -- (Selectivity 1)
AND Application.cid = Company.cid           -- (Selectivity 2)
AND Student.semesters_completed > 6        -- (Selectivity 3)
AND (Student.major='EECS' OR Company.open_roles <= 50) -- (Selectivity 4)
AND NOT Application.status = 'limbo'       -- (Selectivity 5)
ORDER BY Company.open_roles;

```

1. For the following questions, calculate the selectivity of each of the labeled Selectivities above.
 - (a) Selectivity 1
 - (b) Selectivity 2
 - (c) Selectivity 3

(d) Selectivity 4

(e) Selectivity 5

2. For each predicate, which is the first pass of Selinger's algorithm that uses its selectivity to estimate output size? (Pass 1, 2 or 3?)

(a) Selectivity 1

(b) Selectivity 2

(c) Selectivity 3

(d) Selectivity 4

(e) Selectivity 5

3. Mark the choices for all access plans that would be considered in pass 2 of the Selinger algorithm.

(a) Student \bowtie Application (800 IOs)

(b) Application \bowtie Student (750 IOs)

(c) Student \bowtie Company (470 IOs)

(d) Company \bowtie Student (525 IOs)

(e) Application \bowtie Company (600 IOs)

(f) Company \bowtie Application (575 IOs)

4. Which choices from the previous question for all access plans would be chosen at the end of pass 2 of the Selinger algorithm?

5. Which plans that would be considered in pass 3?

(a) Company \bowtie (Application \bowtie Student) (175,000 IOs)

(b) Company \bowtie (Student \bowtie Application) (150,000 IOs)

(c) Application \bowtie (Company \bowtie Student) (155,000 IOs)

- (d) Application \bowtie (Company \bowtie Student) (160,000 IOs)
- (e) Student \bowtie (Company \bowtie Application) (215,000 IOs)
- (f) (Company \bowtie Application) \bowtie Student (180,000 IOs)
- (g) (Application \bowtie Company) \bowtie Student (200,000 IOs)
- (h) (Application \bowtie Student) \bowtie Company (194,000 IOs)
- (i) (Student \bowtie Application) \bowtie Company (195,000 IOs)
- (j) (Student \bowtie Company) \bowtie Application (165,000 IOs)

6. Which choice from the previous question for all plans would be chosen at the end of pass 3?

Query Optimization 2

(Modified from Spring 2016)

1. True or False

- When evaluating potential query plans, the set of left deep join plans are always guaranteed to contain the best plan.
- As a heuristic, the System R optimizer avoids cross-products if possible.
- A plan can result in an interesting order if it involves a sort-merge join.
- The System R algorithm is greedy because for each pass, it only keeps the lowest cost plan for each combination of tables.

2. For the following parts assume the following:

- The System R assumptions about uniformity and independence from lecture hold
- Primary key IDs are sequential, starting from 1

We have the following schema:

CREATE TABLE Flight (fid INTEGER PRIMARY KEY, from_id INTEGER REFERENCES City, to_id INTEGER REFERENCES City, aid INTEGER REFERENCES Airline)	NTuples: 100K, NPages: 50 Index: (I) unclustered B+-tree on aid. 20 leaf pages. (II) clustered B+-tree on (from_cid, fid). 10 leaf pages.
CREATE TABLE City (cid INTEGER PRIMARY KEY, name VARCHAR(16), state VARCHAR(16), population INTEGER)	NTuples: 50K, NPages: 20 Index: (III) clustered B+-tree on population. 10 leaf pages. (IV) unclustered index on cid. 5 leaf pages. Statistics: state in [1, 50], population in [10 ⁶ , 8*10 ⁶]
CREATE TABLE Airline (aid INTEGER PRIMARY KEY, hq_cid INTEGER REFERENCES City, name VARCHAR(16))	NTuples: 5K, NPages: 2

Consider the following query:

```
SELECT *
FROM Flight F, City C, Airline A
WHERE F.to_cid = C.cid
AND F.aid = A.aid
AND F.aid >= 2500
AND C.population > 5e6
AND C.state = 'California';
```

Considering each predicate in the WHERE clause separately, what is the selectivity for each?

- (a) R1: C.state='California'
- (b) R2: F.to_id = C.cid
- (c) R3: F.aid >= 2500
- (d) R4: C.population > 5 * 10⁶

3. For each blank in the System R DP table for Pass 1. Assume this is before the optimizer discards any rows it isn't interested in keeping and note that some blanks may be N/A. Additionally, assume B+ trees are height 2.

Table(s)	Plans	Interesting Orders from Plan (N/A if none)	Cost (I/Os)
Flight	Index (I)		
City	Filescan		
City	Index (III)		

4. After Pass 2, which of the following plans could be in the DP table?

- (a) City [Index(III)] JOIN Airline [File scan]
- (b) City [Index (III)] JOIN Flight [Index (I)]
- (c) Flight [Index (II)] JOIN City [Index (III)]

5. Suppose we want to optimize for queries similar to the query above in part 2, which of the following suggestions could reduce I/O cost?

- (a) Change Index (III) to be unclustered
- (b) Store City as a sorted file on population

